



ASSEMBLY LAYOUT

34.0	34.0	30.0	16
...
22.0	22.0	18.0	10
20.0	20.0	16.0	9
18.0	18.0	14.0	8
16.0	16.0	12.0	7
14.0	14.0	10.0	6
12.0	12.0	8.0	5
9.6	8.6	6.0	4
7.6	6.6	4.0	3
5.6	4.6	2.0	2
C	B	A	PIN

Specifications:

Rated Current	2A AC,DC (AWG #24)				角度	±3°	设计		日期	
Rated Voltage	250V AC,DC				63 < L	±0.3°	审核		日期	
Contact Resistance	10MΩ max				16 < L ≤ 63	±0.2°	核准		日期	
Insulation Resistance	1000MΩ min				4 < L ≤ 16	±0.1°	比例	1:1	视图	
Withstanding Voltage	800V AC/minute				1 < L ≤ 4	±0.05°	单位	MM	页码	1/1
Temperature Range	-25 C to +85 C	胶壳	PA66	白色	L ≤ 1	±0.05°	编号			
Applicable wire Range	AWG #30 to #24	部件	材质	颜色	未详细说明之公差		版本	BY/A2020		

温州柏雨电子有限公司

名称	PH 胶壳
型号	PH-Y