

# Magnet Mount Antennas

## GSM / 3G Applications



**LAMBDOID**  
WIRELESS

Technical Specification		Photograph / Drawing
Model Number	LWC-2400-MM-03 (1.0M-RG58)	
Frequency (MHz)	2400 - 2483 MHz	
Gain	4 dBi	
Impedance ( $\Omega$ )	50	
VSWR	< 2	
Polarization	Linear	
Power Handling (W)	10	
HPBW	H: 360 <sup>0</sup> ; v: 30 <sup>0</sup> / 40 <sup>0</sup>	
Cable Type/ Length	RG58, 1.0m	
Connector	SMA-Plug	
Mechanical Specification		Salient Features
Dimension (mm)	170 x $\phi$ 45 mm	<ul style="list-style-type: none"> <li>- Compact Size</li> <li>- Low Cost</li> <li>- Any cable length</li> <li>- Connector of your choice.</li> </ul>
Housing	Spring Steel Powder Coated	
Weight	<70g	
Environmental Specification		Applications
Operational Temperature	-30 <sup>0</sup> to 60 <sup>0</sup> C	<ul style="list-style-type: none"> <li>- WiFi</li> <li>- Bluetooth</li> <li>- Zigbee</li> <li>- ISM</li> </ul>
Humidity	5 – 75%	

### LAMBDOID WIRELESS COMMUNICATIONS

**Address:** 647/2, 11<sup>th</sup> Main, 5<sup>th</sup> Block, Jayanagar, Bengaluru 560 041. INDIA.

**Tel:** +91 80 2659 5337; **Email:** info@lambdoid.net; **Website:** www.lambdoid.net